NSN 5905-00-834-7290

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-834-7290

Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
0.384 inches
Terminal Length:
Between 0.177 inches and 0.233 inches
Overall Height:
Between 0.365 inches and 0.385 inches
Overall Width:
Between 0.130 inches and 0.228 inches
Mounting Slot Width:
Between 0.062 inches and 0.078 inches
Shaft Diameter:
Between 0.048 inches and 0.076 inches
Shaft Length:
0.035 inches
Body Length:
Between 0.365 inches and 0.385 inches
Body Width:
Between 0.130 inches and 0.228 inches
Body Height:
Between 0.365 inches and 0.385 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Maximum Running Torque:
7.50 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
Between 0.370 inches and 0.422 inches
Mounting Facility Quantity:
2
Terminal Location:

Left adjacent side two rows

NSN 5905-00-834-7290

Precision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Slot
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0