## NSN 5905-00-835-0912

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-835-0912

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Body Diameter:
1.812 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Body Length:
2.062 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:
0.50 inch-ounces
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
84.062 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.80/+0.80 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
3.9 free air single section
Function Conformity Per Section:
Single section proportional conformity
Fixed Tap Quantity Per Section:

6 single section

## NSN 5905-00-835-0912

**Demilitarization:** 

No Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



## **Tap Location Tolerance Per Section:** -1.0/+1.0 ohms single section **Resistance Tolerance Per Section In Percent:** -1.0/+1.0 single section **Actuator Travel Control Feature:** Continuous motion **Tap Location From Ccw Terminal Per Section In Ohms:** 42.031 single section **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Terminal Type And Quantity:** 9 turret Shelf Life: N/a **Unit Of Measure:**