NSN 5905-00-835-2381

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-835-2381 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Overall Length:** 2.140 inches **Body Diameter:** 1.265 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.000 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.000 percent, rated amperes c and better finish **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:**

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 2nd section

NSN 5905-00-835-2381

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Any acceptable
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

No

Fiig:

A002a0