Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-835-3805

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 0.906 inches and 1.000 inches
Body Diameter:
Between 0.890 inches and 0.922 inches
Shaft Diameter:
0.249 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Between 0.437 inches and 0.469 inches
Overall Diameter:
1.274 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
6.00 inch-ounces
Maximum Stop Torque:
128.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.438 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard hushing

Standard bushing

# NSN 5905-00-835-3805

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



#### **Electrical Resistance Per Section:**

1.0 megohms single section

## **Rotary Actuator Travel In Angular Deg:**

Between 251.0 and 318.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

#### **Actuator Travel Control Feature:**

#### Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

C single section

#### **Test Data Document:**

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

3 tab, solder lug

Specification Data:

81349-mil-r-94/4 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0