NSN 5905-00-835-7738

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-835-7738

Electrical Resistance: 82.000 ohms Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
-5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
-55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Encapsulated Terminal Type: Wire lead Reliability Indicator:
Terminal Type: Wire lead Reliability Indicator:
Wire lead Reliability Indicator:
Reliability Indicator:
Not established
Body Diameter:
0.469 inches
Body Length:
2.000 inches
Power Dissipation Rating In Watts:
14.000 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A001a0