NSN 5905-00-835-9555

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-835-9555 **Section Quantity:** 1 **Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established **Overall Length:** 1.578 inches **Overall Height:** 0.406 inches **Overall Width:** 0.359 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.250 inches **Mounting Bushing Length:** 0.130 inches **Body Length:** 1.328 inches **Body Width:** 0.359 inches **Body Height:** 0.313 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Screw Thread Diameter:** 0.216 inches

Screw Thread Series Designator: Unf Screw Thready Qty Per Inch (tpi): 28.0 **Terminal Location:** Lower adjacent side two rows **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 200.000 ohms single section

NSN 5905-00-835-9555

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0