NSN 5905-00-836-0456

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-836-0456 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 4.752 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 100.000 percent, rated amperes c drop siding Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 all sections **Power Dissipation Rating Per Section In Watts:** 2.0 free air all sections **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections **Standard Taper Curve Per Section:** A all sections

NSN 5905-00-836-0456

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal	Type	And	Quantity:

24 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0