

View Online at <https://aerobasegroup.com/nsn/5905-00-836-3717>

Section Quantity:

3

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.0025 inches

Pilot Length:

0.0420 inches

Overall Length:

1.542 inches

Undercut Diameter:

1.030 inches

Undercut Width:

0.0660 inches

Body Diameter:

1.088 inches

Angle Of Mounting Hole In Deg:

135.0

Angle Between Centerlines Of Mounting Holes In Deg:

45.0

Shaft Diameter:

0.125 inches

Shaft Length:

0.458 inches

Body Length:

1.500 inches

Overall Diameter:

1.093 inches

Mounting Lip Diameter:

1.0880 inches

Mounting Lip Depth:

0.0640 inches

Mounting Hole/stud Circle Diameter:

0.436 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

353.0

Maximum Starting Torque:

0.10 inch-ounces

Maximum Running Torque:

0.10 inch-ounces

Screw Thread Diameter:

0.086 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

56.0

Mounting Facility Quantity:

3

Terminal Location:

Rear end

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

5.000 percent, rated amperes c and better select

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 3rd section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-650.0/+650.0 all sections

Power Dissipation Rating Per Section In Watts:

1.5 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

55.0 all sections

Terminal Type And Quantity:

9 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0