## NSN 5905-00-836-6004

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-836-6004

View Online at https://aerobasegroup.com/nsn/5905-00-836-60
Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 1.0295 inches and 1.0300 inches
Pilot Length:
Between 0.0380 inches and 0.0420 inches
Overall Length:
1.062 inches
Undercut Diameter:
Between 0.9975 inches and 1.0025 inches
Undercut Width:
Between 0.0580 inches and 0.0660 inches
Body Diameter:
Between 1.057 inches and 1.067 inches
Angle Of Mounting Hole In Deg:
60.0
Angle Between Centerlines Of Mounting Holes In Deg:
120.0
Shaft Diameter:
0.125 inches
Shaft Length:
0.500 inches
Body Length:
0.562 inches
Overall Diameter:
1.281 inches
Mounting Lip Diameter:
Between 1.0880 inches and 1.0930 inches
Mounting Lip Depth:
Between 0.0560 inches and 0.0640 inches
Mounting Hole/stud Circle Diameter:
Between 0.436 inches and 0.438 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:

353.0

## NSN 5905-00-836-6004

Precision Wire Wound Variable Resistor - Page 2 of 3



Market and Occupant of Taxable
Maximum Starting Torque:
0.075 inch-ounces
Screw Thread Diameter:
0.086 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
56.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
2.500 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-650.0/+650.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 heat sink single section
Function Conformity Per Section:
Single section terminal base linearity
Resistance Tolerance Per Section In Percent:
-3.0/+7.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Unit Of Measure:

-

## NSN 5905-00-836-6004

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0