Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-836-7714

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

0.484 inches

#### Shaft Diameter:

0.156 inches

#### Shaft Length:

0.500 inches

Mounting Bushing Length:

0.375 inches

#### Body Length:

# 0.344 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### Mounting Method:

Locking bushing

#### **Features Provided:**

Nonmetallic shaft

#### **Electrical Resistance Per Section:**

2.0 megohms single section

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

## **Power Dissipation Rating Per Section In Watts:**

0.2 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section



### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

### Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A002a0