## NSN 5905-00-836-7849

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-836-7849 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.0300 inches Pilot Length: 0.0400 inches **Overall Length:** 1.531 inches **Undercut Diameter:** 1.0025 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.093 inches **Angle Of Mounting Hole In Deg:** 90.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Body Length:** 1.031 inches **Overall Diameter:** 1.500 inches **Mounting Lip Diameter:** 1.0930 inches **Mounting Lip Depth:** 0.0600 inches **Mounting Hole/stud Circle Diameter:** 0.437 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing

**Actuator Type:** 

Single shaft

## NSN 5905-00-836-7849

Precision Wire Wound Variable Resistor - Page 2 of 3



Effective Electrical Rotation In Deg Angular Rotation:
353.0
Maximum Starting Torque:
0.125 inch-ounces
Fragility Factor:
Moderately delicate
Screw Thread Diameter:
0.086 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
56.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring and threaded hole
Electrical Resistance Per Section:
2.500 percent, rated amperes c and better finish
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.20/+0.20 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-650.0/+650.0 all sections
Power Dissipation Rating Per Section In Watts:
1.5 heat sink all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+7.0 1st section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 all sections
Terminal Type And Quantity:
6 turret
Shelf Life:

N/a

## NSN 5905-00-836-7849

Precision Wire Wound Variable Resistor - Page 3 of 3



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0