Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-837-3509

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.562 inches **Overall Width:** Between 0.328 inches and 0.359 inches Shaft Diameter: 0.115 inches Shaft Length: 0.250 inches Mounting Bushing Length: 0.250 inches **Body Length:** Between 1.297 inches and 1.328 inches **Body Height:** Between 0.312 inches and 0.344 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Screw Thread Diameter:** 0.216 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 50.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0 **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

NSN 5905-00-837-3509

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:

Stops

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0