

View Online at <https://aerobasegroup.com/nsn/5905-00-837-3511>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.469 inches

**Body Diameter:**

Between 1.094 inches and 1.312 inches

**Shaft Diameter:**

Between 0.185 inches and 0.263 inches

**Shaft Length:**

Between 1.031 inches and 1.531 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

Between 0.953 inches and 0.984 inches

**Shaft Style:**

Round

**Actuator Type:**

Dual concentric

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

25.0 percent, rated amperes c and better industrial clears

**Rotary Actuator Travel In Angular Deg:**

315.0

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 all sections

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0