## NSN 5905-00-837-3512

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-837-3512

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Rectangular w/bushing   |
| Reliability Indicator:  |
| Not established   |
| Shaft Diameter:   |
| 0.115 inches  |
| Shaft Length:   |
| 0.250 inches  |
| Mounting Bushing Length:  |
| 0.250 inches  |
| Body Length:  |
| Between 1.297 inches and 1.328 inches                                       |
| Body Width:   |
| 0.312 inches  |
| Body Height:  |
| Between 0.312 inches and 0.344 inches                                       |
| Shaft Style:  |
| Round, slotted  |
| Actuator Type:  |
| Single shaft  |
| Effective Electrical Rotation In Deg Angular Rotation:                      |
| 9000.0  |
| Screw Thread Diameter:  |
| 0.216 inches  |
| Screw Thread Series Designator:   |
| Unef  |
| Screw Thready Qty Per Inch (tpi):   |
| 32.0  |
| Terminal Location:  |
| Lower adjacent side single row  |
| Mounting Method:  |
| Standard bushing  |
| Features Provided:  |
| Humidity proof  |
| Electrical Resistance Per Section:  |
| 1.000 kilohms single section  |
| Rotary Actuator Travel In Angular Deg:                                      |
| 9000.0  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
|   |

125.0 single section

## NSN 5905-00-837-3512

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No