## NSN 5905-00-837-3585

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-837-3585 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.030 inches **Body Length:** 1.340 inches **Body Width:** 0.300 inches **Body Height:** 0.360 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7920.0 **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 500.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 7920.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-800.0/+50.0 single section

## NSN 5905-00-837-3585

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: