NSN 5905-00-838-1266

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-838-1266

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 1.281 inches and 1.375 inches
Body Diameter:
Between 0.890 inches and 0.922 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
Between 0.840 inches and 0.906 inches
Mounting Bushing Length:
Between 0.484 inches and 0.516 inches
Body Length:
Between 0.437 inches and 0.469 inches
Overall Diameter:
1.274 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
6.00 inch-ounces
Maximum Stop Torque:
128.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
Between 0.422 inches and 0.454 inches
Longitudinal Actuator Travel:
0.12 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef

Terminal Location:

32.0

Screw Thready Qty Per Inch (tpi):

Radially positioned over less than half the circumference

NSN 5905-00-838-1266

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Locking bushing
Electrical Resistance Per Section:
50.0 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/4 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: