NSN 5905-00-838-1883

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-838-1883 **Section Quantity:** 1 **Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established **Overall Length:** 1.562 inches **Overall Width:** Between 0.328 inches and 0.359 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.030 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** Between 1.297 inches and 1.328 inches **Body Width:** 0.300 inches **Body Height:** Between 0.312 inches and 0.344 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7920.0 **Screw Thread Diameter:** 0.216 inches **Screw Thread Series Designator:**

Screw Thready Qty Per Inch (tpi): 28.0 **Terminal Location:** Lower adjacent side two rows **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 2.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 7920.0

NSN 5905-00-838-1883

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-500.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0