NSN 5905-00-838-3905

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-838-3905

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.87000 inches and 1.88000 inches

Pilot Length:

Between 0.05700 inches and 0.06700 inches

Overall Length:

Between 1.556 inches and 1.598 inches

Undercut Diameter:

Between 1.870 inches and 1.880 inches

Undercut Width:

Between 0.07300 inches and 0.08300 inches

Body Diameter:

Between 1.995 inches and 2.005 inches

Shaft Diameter:

Between 0.249 inches and 0.250 inches

Shaft Length:

Between 0.546 inches and 0.578 inches

Body Length:

Between 1.010 inches and 1.020 inches

Overall Diameter:

Between 1.995 inches and 2.005 inches

Mounting Lip Diameter:

Between 1.99500 inches and 2.00500 inches

Mounting Lip Depth:

Between 0.05700 inches and 0.06700 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

358.0

Maximum Starting Torque:

1.50 inch-ounces

Maximum Running Torque:

0.80 inch-ounces

Terminal Location:

Radially positioned over less than half the circumference

NSN 5905-00-838-3905

Precision Wire Wound Variable Resistor - Page 2 of 2



| Mounting Method: |
|---|
| Flange |
| Features Provided: |
| Nonmetallic shaft |
| Electrical Resistance Per Section: |
| 10.000 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Function Conformity Tolerance Per Section: |
| -0.10/+0.10 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.5 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Fixed Tap Quantity Per Section: |
| 1 single section |
| Resistance Tolerance Per Section In Percent: |
| -3.0/+3.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Function Characteristic Per Section: |
| Single section linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 80.0 single section |
| Terminal Type And Quantity: |
| 3 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |