NSN 5905-00-838-9210

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-838-9210 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 1.030 inches and 1.070 inches **Terminal Length:** 1.500 inches **Overall Height:** Between 0.305 inches and 0.325 inches **Mounting Hole Diameter:** 0.087 inches **Shaft Diameter:** Between 0.125 inches and 0.140 inches **Shaft Length:** Between 0.050 inches and 0.060 inches **Body Length:** Between 0.990 inches and 1.110 inches **Body Width:** Between 0.160 inches and 0.180 inches **Body Height:** 0.315 inches **Shaft Style:** Round, slotted **Contact Arm Electrical Off Position:** Fully ccw-cw **Actuator Type:** Single shaft **Maximum Starting Torque:** 5.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.750 inches and 0.755 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

200.0 ohms single section

Electrical Resistance Per Section:

NSN 5905-00-838-9210

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
5400.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Gold plated copperweld wire terminals
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig: