Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-838-9417

1

- **Reliability Indicator:**
- Not established
- First Flat Length:
- 0.344 inches
- Flat Height:
- 0.094 inches
- Shaft Diameter:
- 0.125 inches
- Shaft Length:
- 3.000 inches
- Shaft Style:
- Round, flatted
- **Contact Arm Electrical Off Position:**
- Fully ccw
- Actuator Type:
- Single shaft
- Nonturn Device Location:
- At 6 oclock
- Nonturn Device Radius:
- 0.250 inches
- Screw Thread Diameter:
- 0.250 inches
- Screw Thread Series Designator:
- Unef
- Screw Thready Qty Per Inch (tpi):
- 32.0
- Mounting Method:
- Standard bushing
- **Electrical Resistance Per Section:**
- 15.0 ohms single section
- **Power Dissipation Rating Per Section In Watts:**
- 12.5 free air single section
- **Resistance Tolerance Per Section In Percent:**
- -10.0/+10.0 single section
- Standard Taper Curve Per Section:
- A single section
- **Terminal Type And Quantity:**
- 3 tab, solder lug
- Shelf Life:
- N/a

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0