NSN 5905-00-839-1139

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-839-1139

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Overall Length:

Between 0.515 inches and 0.555 inches

Terminal Length:

Between 0.187 inches and 0.202 inches

Overall Height:

Between 0.490 inches and 0.510 inches

Overall Width:

Between 0.387 inches and 0.472 inches

Mounting Hole Diameter:

Between 0.063 inches and 0.083 inches

Shaft Diameter:

Between 0.071 inches and 0.088 inches

Shaft Length:

Between 0.025 inches and 0.045 inches

Body Length:

Between 0.490 inches and 0.510 inches

Body Width:

Between 0.200 inches and 0.270 inches

Body Height:

Between 0.490 inches and 0.510 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9360.0

Maximum Starting Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.190 inches and 0.210 inches

Lateral Distance Between Mounting Hole Centers:

0.519 inches

Mounting Facility Quantity:

2

Terminal Location:

Left adjacent side two rows

NSN 5905-00-839-1139

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Mounting Method: |
|---|
| Unthreaded hole |
| Center To Center Distance Between Terminal Rows: |
| 0.100 inches |
| Electrical Resistance Per Section: |
| 5.000 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 9360.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| Between 0.095 inches and 0.105 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -400.0/+400.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.75 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |
| Clutch |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |