

View Online at <https://aerobasegroup.com/nsn/5905-00-839-2237>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.8740 inches and 1.8750 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Undercut Diameter:

1.874 inches

Undercut Width:

0.0930 inches

Body Diameter:

Between 1.874 inches and 1.875 inches

Shaft Diameter:

Between 0.249 inches and 0.250 inches

Shaft Length:

Between 0.844 inches and 0.906 inches

Body Length:

2.156 inches

Mounting Lip Diameter:

Between 1.9950 inches and 2.0050 inches

Mounting Lip Depth:

Between 0.0570 inches and 0.0670 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Maximum Starting Torque:

1.50 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Shaft End Play:

0.002 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Flange

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Power Dissipation Rating Per Section In Watts:

0.8 free air single section

Function Conformity Per Section:

Single section terminal base linearity

Resistance Tolerance Per Section In Percent:

-1.0/+1.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0