NSN 5905-00-840-1044

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-840-1044

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.220 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.620 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 290.0 and 305.0
Nonturn Device Location:
Nonturn Device Location: At 9 oclock
At 9 oclock
At 9 oclock Nonturn Device Radius:
At 9 oclock Nonturn Device Radius: 0.531 inches
At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter:
At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches
At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator:
At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef
At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0
At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference
At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method:
At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Locking bushing
At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Locking bushing Electrical Resistance Per Section:

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

NSN 5905-00-840-1044

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-19 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-19/2 government specification
Departure From Cited Designator:
Quality controlled for polaris
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: