NSN 5905-00-840-5280

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-840-5280

Electrical Resistance: 47.000 ohms Resistance Tolerance In Percent: 5.000/45.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 45.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 47.5.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0 Inclosure Method: 61.000 Inclosure Method: 61.000 Inclosure Method: 62.000 Inclosure Method: 63.000 Incl	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
47.000 ohms Resistance Tolerance In Percent: 5.000/4-5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 175.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-275.0 Tempurature Range Of Tempurature In Deg Celsius At Zero Percent Rated Power: 57.0/4-275.0 Tempurature Range Of Tempurature In Deg Celsius At Zero Percent Rated Power: 57.0/4-275.0 Tempurature Range Of Tempurature In Deg Celsius At Zero Percent Rated Power: 57.0/4-275.0 Tempurature Range Of Tempurature In Deg Celsius At Full Rated Power: 57.0/4-275.0 Tempurature Range Of Tempurature In Deg Celsius At Full Rated Power: 57.0/4-275.0 Tempurature Range Of Tempurature Rated Power: 57.0/4-275.0 Tempurature Rated Power: 57.0/4-275.0 Tempurature Range Of Tempurature Rated Power: 57.0/4-275.0 Tempurature Rat	-150.0/+150.0
Resistance Tolerance in Percent: 5.000/45.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 5.000 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 775.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 775.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature In Deg Celsius At Zero Percent Rated Power: 55.0/+275.0 Tempurature Range Of Tempurature In Deg Celsius At Zero Percent Rated Power: 55.0/+275.0 Tempurature Range Of Tempurature In Deg Celsius At Zero Percent Rated Power: 55.0/+275.0 Tempurature Range Of Tempurature In Deg Celsius At Zero Percent Rated Power: 55.0/+275.0 Tempurature Range Of Tempurature In Deg Celsius At Zero Percent Rated Power: 55.0/+275.0 Tempurature Range Of Tempurature In Deg Celsius At Zero Percent Rated Power: 55.0/+275.0 Tempurature Range Of Tempurature In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Rated Power: 55.0/+275.0 Tempurature Rated Power: 55.0/+275.0 Tempurature Rated Power: 55	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 15.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Inclosure Method: 15.0acapsulated Terminal Type: 15.0acapsulated Terminal Type: 15.0acapsulated 15.0acapsulate	147.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 Inclosure Method: Incapsulated Iteminal Type: Iteminal Itemi	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/4275.0 Inclosure Method: In	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0+275.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Rody Diameter: 1.313 inches Rody Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Roty Designator: Exist terminal each end Test Data Document: 14385-96451721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2xcludes any specification, standard or other document that may be referenced in a basic governing drawing) Rother Life: Wire Designator: 14385-9641721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2xcludes any specification, standard or other document that may be referenced in a basic governing drawing) Rother Life: Wire Demilitarization:	Ambient Tempurature In Deg Celsius At Full Rated Power:
rempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 nclosure Method: ncapsulated ferminal Type: Vire lead Reliability Indicator: Alot established 30dy Diameter: 3.313 inches 30dy Length: .000 inches Power Dissipation Rating In Watts: £000 free air ### Style Designator: xxial terminal each end feet Data Document: ixial terminal each end feet Data Document ixial terminal end f	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Alot established Body Diameter: 3.313 inches Body Length: 4.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Avail terminal each end Test Data Document: 14959-9a51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 24959-9a51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 34959-9a51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 34959-9a51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 34959-9a51721 drawing (this is the basic governing drawing) 35heff Life: 340 341 341 342 343 344 345 346 346 347 348 348 349 340 340 340 340 340 340 340	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Sody Diameter:313 inches Sody Length:000 inches Power Dissipation Rating In Watts:000 free air Style Designator:xial terminal each end Fest Data Document:4959-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;xiculdes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	275.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Reliability Indicator: Not Designator: Not Indicator: Not Ind	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Vire lead Reliability Indicator: Not established Reliability Indicator: Not planeter: N	-55.0/+275.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.500 free air Style Designator: 1.514359-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: 1.5250-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: 1.5260-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: 1.5260-ga51721 drawing (this is the dasic governing drawing) 1.5361-ga51721 drawing (this is the dasic governing drawing)	Inclosure Method:
Nice lead Reliability Indicator: Not established Redy Diameter:	Encapsulated
Reliability Indicator: Not established Redy Diameter: 0.313 inches Redy Length: 0.000 inches Power Dissipation Rating In Watts: 0.000 free air Retyle Designator: Exist terminal each end Rest Data Document: 0.4959-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 0.001 exist Life: 0.402 0.001 free air 0.002 free air 0.003 free air 0.003 free air 0.003 free air 0.003 free air 0.004 free air 0.005 free air 0.005 free air 0.006 free air 0.007 free air 0.008 free air 0.008 free air 0.008 free air 0.008 free air 0.009 free air 0.009 free air 0.009 free air 0.000 free ai	Terminal Type:
Note established Rody Diameter: 2.313 inches Rody Length: 2.000 inches Power Dissipation Rating In Watts: 2.000 free air Riyle Designator: Axial terminal each end Post Data Document: 2.4959-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2.4x10 excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure: Demilitarization:	Wire lead
Body Length:000 inches Power Dissipation Rating In Watts:000 free air Style Designator:xial terminal each end Fest Data Document:xial terminal (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;xialteriesxialt	Reliability Indicator:
Body Length:000 inches Power Dissipation Rating In Watts:000 free air Style Designator:	Not established
Body Length: .000 inches Power Dissipation Rating In Watts: .000 free air Style Designator: .xxial terminal each end Fest Data Document: .xxial terminal each end Style Style Designator: .xxial terminal each end Fest Data Document: .xxial terminal	Body Diameter:
Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Fest Data Document: 64959-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 6xecludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: A/a Jinit Of Measure: Demilitarization:	0.313 inches
Power Dissipation Rating In Watts: 5,000 free air 6tyle Designator: Axial terminal each end Fest Data Document: 64959-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) 6thelf Life: Al/a Unit Of Measure: Demilitarization:	Body Length:
Style Designator: Axial terminal each end Fest Data Document: S4959-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: A/a Unit Of Measure: Demilitarization:	1.000 inches
Axial terminal each end Test Data Document: 64959-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: A/a Unit Of Measure: Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 64959-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) 6helf Life: 1/4 1/4 1/6 Measure: 1- 1/8 1/8 1/8 1/8 1/8 1/8 1/8	5.000 free air
Fest Data Document: 64959-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Demilitarization:	Style Designator:
34959-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Demilitarization:	Test Data Document:
Shelf Life: N/a Unit Of Measure: - Demilitarization:	64959-ga51721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
√a Jnit Of Measure: - Demilitarization:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Jnit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
iia:	No
	Fiig:
N001a0	A001a0