Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-840-5445

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.750 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.750 inches

## Mounting Bushing Length:

0.250 inches

## Body Length:

## 0.468 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

295.0

## Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.234 inches

#### Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

5.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

295.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# NSN 5905-00-840-5445

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

1.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

# Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

## Fiig:

A002a0