

View Online at <https://aerobasegroup.com/nsn/5905-00-840-7884>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

1.578 inches

Terminal Length:

0.188 inches

Overall Height:

0.579 inches

Overall Width:

0.359 inches

Mounting Hole Diameter:

0.088 inches

Body Length:

1.328 inches

Body Width:

0.359 inches

Body Height:

0.391 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Maximum Starting Torque:

7.50 inch-ounces

Center To Center Distance Between Terminals:

0.688 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Screw Thread Diameter:

0.216 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

28.0

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side single row

Mounting Method:

Standard bushing and unthreaded hole

Electrical Resistance Per Section:

1.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.328 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Bushing lg 0.250 inch

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0