## NSN 5905-00-841-0398

**Section Quantity:** 

Cylindrical bushing mounted

Reliability Indicator:

Not established

**Body Style:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-841-0398

Overall Length:	
2.000 inches	
Body Diameter:	
1.562 inches	
Shaft Diameter:	
0.250 inches	
Shaft Length:	
0.625 inches	
Mounting Bushing Length:	
0.500 inches	
Body Length:	
1.375 inches	
Shaft Style:	
Round, slotted	
Shaft Bearing Type:	
Bearing	
Actuator Type:	
Single shaft	
Nonturn Device Location:	
At 6 oclock	
Nonturn Device Radius:	
0.500 inches	
Screw Thread Diameter:	
0.375 inches	
Screw Thread Series Design	nator:
Unef	
Screw Thready Qty Per Inch	ı (tpi):
32.0	
Mounting Method:	
Locking bushing	
Electrical Resistance Per Se	ection:
100.000 ohms single section	
Power Dissipation Rating P	er Section In Watts:
25.0 free air single section	
Function Conformity Per Se	ection:
Single section independent lin	earity

## NSN 5905-00-841-0398

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance	<b>Tolerance</b>	Per	Section	In	Percent:

-10.0/+10.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0