NSN 5905-00-841-8249

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-841-8249

Electrical Resistance: 1,000 magehms Resistance Tolerance In Percent: 1,000/+1,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Range Of Tempurature Coefficient In Deg Celsius: 165.0/+145.0 Inclosure Method: Incapsulated Reliability Indicator: 160 and Statistics Incapsulated Reliability Indicator: 161 and Statistics Incapsulated Reliability Indicator: 162 and Degrater 163 and Degrater 163 and Degrater 163 and Degrater 164 and Degrater 165 and Degr	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: 1,000/4-1,000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 45.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 65.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 66.0/4-145.0 Tempurature Rende Of Tempurature Coefficient in Deg Celsius: 67.0/4-145.0 Tempurature Rende Of Tem	-20.0/+20.0
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0/+145.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Note established 30dy Diameter: 1.0375 inches 30dy Length: 1.000 inches Power Dissipation Rating In Watts: 1.500 free air Style Designator: Axial terminal each end Test Data Document: 1xial-smiral/3/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Dirti Of Measure: - Demilitarization: No	Electrical Resistance:
1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Rody Diameter: 1.375 inches Rody Length: 1.000 inches Power Dissipation Rating In Watts: 1.550 free air Ryle Designator: 1.5149-milr@3/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: Via Unit of Measure: - Demillitarization: No	1.000 megohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Empurature Range Of Tempurature Coefficient In Deg Celsius: 165.0/+145.0 Inclosure Method: Emparature Method: Emparature Range Of Tempurature Coefficient In Deg Celsius: 165.0/+145.0 Inclosure Method: Emparature Met	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 445.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 noticesure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 30.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.550 free air Style Designator: Availa terminal each end Test Data Document: 13349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Unit Of Measure: - Demilitarization: No	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Incapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.550 free air Style Designator: Avial terminal each end Fest Data Document: 191349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Julit Of Measure: Demilitarization:	Ambient Tempurature In Deg Celsius At Full Rated Power:
rempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 inclosure Method: incapsulated ferminal Type: Wife lead Reliability Indicator: Not established Body Diameter: 1.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.500 free air Style Designator: Axial terminal each end fest Data Document: 11349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Value Juit Of Measure: Demilitarization:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches 0.3075 inches 0.309 Length: 0.000 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Exist Eminal each end Test Data Document: 81349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Va Juit Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 3.375 inches 3.364 Length: 1.000 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: xixial terminal each end Fest Data Document: 81349-militg3/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Va Juit Of Measure:	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.000 inches Power Dissipation Rating in Watts: 0.500 free air Style Designator: Wital terminal each end Fest Data Document: 11349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: - Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.000 inches Power Dissipation Rating In Watts: 0.500 free air Skyle Designator: Value Toology and Pocument: 81349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Va Unit Of Measure: - Demilitarization:	-65.0/+145.0
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.375 inches Body Length: 10.000 inches Power Dissipation Rating In Watts: 10.500 free air Style Designator: Exial terminal each end Fest Data Document: 181349-milir93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Va Unit Of Measure: - Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Not established Rody Diameter: 0.375 inches Rody Length: 0.000 inches Power Dissipation Rating In Watts: 0.500 free air Relyle Designator: Avial terminal each end Rest Data Document: 0.349-milir93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Va Unit Of Measure: - Demilitarization:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: - Demilitarization:	Terminal Type:
Note established Body Diameter:	Wire lead
Body Length: 2.375 inches Body Length: 2.000 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: Axial terminal each end Fest Data Document: 2.31349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization:	Reliability Indicator:
375 inches 380dy Length: 1.000 inches 290wer Dissipation Rating In Watts: 1.500 free air 38tyle Designator: Axial terminal each end 1955 Data Document: 181349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 1825 excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). 1836 Shelf Life: 1840 1850 1861 Life: 1860 1860 1860 1860 1860 1860 1860 1860	Not established
Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.500 free air Style Designator: Axial terminal each end Fest Data Document: 1.51349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Diameter:
Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 0.1349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: - Demilitarization:	0.375 inches
Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization:	Body Length:
Style Designator: Axial terminal each end Fest Data Document: B1349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	1.000 inches
Style Designator: Axial terminal each end Fest Data Document: B1349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 31349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	0.500 free air
Fest Data Document: 81349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Style Designator:
B1349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization:	81349-milr93/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Unit Of Measure: - Demilitarization:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
No W/a Jnit Of Measure: - Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Filg:	No
	Fiig:
A001a0	A001a0