

View Online at https://aerobasegroup.com/nsn/5905-00-842-5949

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.203 inches

#### Body Diameter:

0.500 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.750 inches

#### Mounting Bushing Length:

## 0.500 inches

**Body Length:** 

0.453 inches

Shaft Style:

Round, slotted

#### Shaft Bearing Type:

Bearing

#### Actuator Type:

Single shaft

#### Nonturn Device Location:

At 3 oclock and at 9 oclock

#### Nonturn Device Radius:

0.245 inches

#### Screw Thread Diameter:

0.250 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# Mounting Method:

Locking bushing

# Electrical Resistance Per Section:

10.000 percent, rated amperes c and better flooring

# Power Dissipation Rating Per Section In Watts:

0.5 7th secondary quality

# Function Conformity Per Section:

Single section independent linearity



**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0