NSN 5905-00-842-8939

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-842-8939 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.8740 inches and 1.8750 inches Pilot Length: Between 0.3100 inches and 0.9300 inches **Overall Length:** 1.807 inches **Undercut Diameter:** Between 1.874 inches and 1.875 inches **Undercut Width:** 0.0760 inches **Body Diameter:** Between 1.969 inches and 2.031 inches **Angle Of Mounting Hole In Deg:** 0.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.657 inches **Body Length:** 0.995 inches **Overall Diameter:** 2.250 inches **Mounting Lip Diameter:** Between 1.9690 inches and 2.0310 inches **Mounting Lip Depth:** Between 0.0620 inches and 0.1240 inches **Mounting Hole/stud Circle Diameter:** Between 1.219 inches and 1.281 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:**

Single shaft

NSN 5905-00-842-8939

Precision Wire Wound Variable Resistor - Page 2 of 3



Effective Electrical Rotation In Deg Angular Rotation:
352.0
Maximum Starting Torque:
1.00 inch-ounces
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
3.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-842-8939

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0