## NSN 5905-00-842-9659

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-842-9659

### Section   February   ### Section   February   ### Section   February   ### Section   February   ### Section   ### Section
4.990 kilohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0  Inclosure Method: Encapsulated Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.375 inches  Body Length: 1.780 inches  Power Dissipation Rating In Watts: 10.000 free air  Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.375 inches  Body Length: 1.780 inches  Power Dissipation Rating In Watts: 10.000 free air  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.375 inches  Body Length:  1.780 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.375 inches  Body Length: 1.780 inches  Power Dissipation Rating In Watts: 10.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.375 inches  Body Length:  1.780 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Not established  Body Diameter: 0.375 inches  Body Length: 1.780 inches  Power Dissipation Rating In Watts: 10.000 free air  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Body Diameter:  0.375 inches  Body Length:  1.780 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
0.375 inches  Body Length:  1.780 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Body Length:  1.780 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
1.780 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
10.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical". "average". "". etc.).
, , , , , , , , , , , , , , , , , , ,
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0