NSN 5905-00-842-9766

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-842-9766 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 4.396 inches and 4.416 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** Between 0.865 inches and 0.885 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 2.656 inches **Overall Diameter:** 2.125 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.531 inches **Shaft End Play:** 0.01000 inches **Shaft Runout:** 0.002 inches

Pilot Diameter Runout:

0.00300 inches

NSN 5905-00-842-9766

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.003 inches
Fragility Factor:
Moderately delicate
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing and standard bushing
Electrical Resistance Per Section:
100.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-45.0/+45.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 7th secondary quality
Function Conformity Per Section:
Single section absolute linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Features:
0.375 in. Long bushing both ends
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

NSN 5905-00-842-9766

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0