

View Online at <https://aerobasegroup.com/nsn/5905-00-843-3270>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes/slots

**Reliability Indicator:**

Not established

**Overall Length:**

1.248 inches

**Terminal Length:**

12.000 inches

**Overall Height:**

Between 0.302 inches and 0.322 inches

**Overall Width:**

Between 0.180 inches and 0.200 inches

**Mounting Hole Diameter:**

0.086 inches

**Shaft Diameter:**

Between 0.100 inches and 0.130 inches

**Shaft Length:**

Between 0.065 inches and 0.085 inches

**Body Length:**

Between 1.163 inches and 1.183 inches

**Body Width:**

Between 0.180 inches and 0.200 inches

**Body Height:**

Between 0.302 inches and 0.322 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

7.50 inch-ounces

**Lateral Distance Between Mounting Hole Centers:**

Between 0.990 inches and 1.010 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Rear end

**Mounting Method:**

Unthreaded hole

**Electrical Resistance Per Section:**

150.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

9000.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

200.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

75.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0