NSN 5905-00-843-3308

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-843-3308

-15.0/415.0 Electrical Resistance: 90.000 kilohms Resistance Tolerance in Percent: -0.100/+0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Resilability Indicator: Not established Body Longth: 0.500 inches Body Width: 0.250 inches Body Width: 0.250 inches Power Dissipation Rating in Watts: 0.250 free air Syle Designator: Terminals one edge Tests Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
80.000 kilohms Resistance Tolerance In Percent: -0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.500 inches Body Width: 0.250 inches Body Width: 0.250 inches Body Height: 0.250 inches Flower Dissipation Rating In Watts: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminal Sone edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	-15.0/+15.0
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Body Length: 0.500 inches Body Width: 0.250 inches Body Height: 0.250 inches Body Height: 0.250 inches Sover Dissipation Rating In Watts: 0.250 inches Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Na Unit Of Measure:	Electrical Resistance:
-0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.250 inches Body Width: 0.250 inches Body Width: 0.250 inches Sody Height: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	90.000 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.550 inches Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Na Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.500 inches Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-442-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: — Demilitarization: No Flig:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.500 inches Body Width: 0.250 inches Body Width: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.500 inches Body Width: 0.250 inches Body Weight: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 inche air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.500 inches Body Width: 0.250 inches Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-56.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.500 inches Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 inches Power Dissipation Rating In Watts: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	145.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.500 inches Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.500 inches Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 inches Priminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+125.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.500 inches Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Length: 0.500 inches Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Body Length: 0.500 inches Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note established Body Length: 0.500 inches Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Length: 0.500 inches Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
0.500 inches Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Width: 0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
0.250 inches Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.500 inches
Body Height: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Width:
0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 inches
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Height:
O.250 free air Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 inches
Style Designator: Terminals one edge Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Test Data Document: 94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminals one edge
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	94756-443-0135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0