NSN 5905-00-844-2289

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-844-2289 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.312 inches **Terminal Length:** 11.500 inches **Overall Height:** Between 0.297 inches and 0.328 inches **Overall Width:** Between 0.217 inches and 0.249 inches **Mounting Hole Diameter:** 0.088 inches **Shaft Diameter:** 0.093 inches **Shaft Length:** Between 0.047 inches and 0.078 inches **Body Length:** Between 1.234 inches and 1.266 inches **Body Width:** Between 0.217 inches and 0.249 inches **Body Height:** Between 0.297 inches and 0.328 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 7.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:**

Terminal Location: Rear end **Mounting Method:** Unthreaded hole **Features Provided:** Nonmetallic shaft

NSN 5905-00-844-2289

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:	
2.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
7920.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
175.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.8 free air single section	
Resistance Tolerance Per Section In Percent:	
-5.0/+5.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 wire lead	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Filig:	
A002a0	