

View Online at <https://aerobasegroup.com/nsn/5905-00-844-4083>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

liilength:

Between 1.547 inches and 1.578 inches

Body Diameter:

Between 0.672 inches and 0.703 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.812 inches

Body Length:

Between 0.656 inches and 0.688 inches

liidiameter:

2.062 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.516 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

10.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Stops

Special Features:

0.625 inch long bushing

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0