

View Online at <https://aerobasegroup.com/nsn/5905-00-844-4083>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**liilength:**

Between 1.547 inches and 1.578 inches

**Body Diameter:**

Between 0.672 inches and 0.703 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.812 inches

**Body Length:**

Between 0.656 inches and 0.688 inches

**liidiameter:**

2.062 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

Between 0.516 inches and 0.547 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Mounting Method:**

Locking bushing

**Electrical Resistance Per Section:**

10.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

300.0

**Power Dissipation Rating Per Section In Watts:**

3.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

**Actuator Travel Control Feature:**

Stops

**Special Features:**

0.625 inch long bushing

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0