## NSN 5905-00-844-6360

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-844-6360 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.030 inches **Body Diameter:** 1.812 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 1.218 inches **Overall Diameter:** 2.030 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1080.0 **Maximum Starting Torque:** 1.75 inch-ounces **Maximum Running Torque:** 1.25 inch-ounces **Nonturn Device Location:** 

At 12 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.010 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.005 inches

## NSN 5905-00-844-6360

Precision Wire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
1080.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a

N/a

## NSN 5905-00-844-6360

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A002a0