## NSN 5905-00-844-7202

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-844-7202

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -500.0/+200.0   -500.0/+200.0   -500.0/+200.0   -500.0/+200.0   -500.0/+200.0   -500.0/+200.0   -500.0/+200.0   -500.0/+200.0   -5
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+85.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.688 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+85.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Dlameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.220 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+85.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.688 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga63314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+85.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.220 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+85.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.220 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+85.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.220 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+85.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 1.500 inches and 0.280 inches Body Diameter: Between 0.688 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+85.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 1.500 inches and 0.280 inches Body Diameter: Between 0.688 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.688 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.688 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:
Hermetically sealed  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 1.500 inches and 1.625 inches  Body Diameter:  Between 0.220 inches and 0.280 inches  Body Length:  Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 1.500 inches and 1.625 inches  Body Diameter:  Between 0.220 inches and 0.280 inches  Body Length:  Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 1.500 inches and 1.625 inches  Body Diameter:  Between 0.220 inches and 0.280 inches  Body Length:  Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Reliability Indicator: Not established  Terminal Length: Between 1.500 inches and 1.625 inches  Body Diameter: Between 0.220 inches and 0.280 inches  Body Length: Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Not established  Terminal Length: Between 1.500 inches and 1.625 inches  Body Diameter: Between 0.220 inches and 0.280 inches  Body Length: Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:  Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Terminal Length: Between 1.500 inches and 1.625 inches  Body Diameter: Between 0.220 inches and 0.280 inches  Body Length: Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Between 1.500 inches and 1.625 inches  Body Diameter:  Between 0.220 inches and 0.280 inches  Body Length:  Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Between 0.220 inches and 0.280 inches  Body Length:  Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:  Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Between 0.220 inches and 0.280 inches  Body Length:  Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:  Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:  Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:  Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
O.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Style Designator:  Axial terminal each end  Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:
64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0