## NSN 5905-00-845-4164

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-845-4164

Electrical Resistance: 1.530 klohms Resistance Tolerance In Percent: 1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 17.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 15.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 15.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 15.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 15.0 to 15.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 15.	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: 1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 150.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 remous Method: Hermelically sealed Terminal Type: Write lead Reliability Indicator: Not established Terminal Length: 1.500 inches 380dy Diameter: 2.250 inches 380dy Diameter: 2.250 inches 380dy Diameter: 2.250 inches 380dy Length: 2.750 inches 381d terminal each end Test Data Document: 381876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 381616 Life: 382 38361 Life Celsius Celsius Celsius At Full Rated Power: 38361 Life Celsius Celsius At Full Rated Power: 38361 Life Celsius Celsius At Full Rated Power: 38361 Life Celsius At Full Rated Power: 38362 Life Cels	-500.0 to 200.0
Resistance Tolerance in Percent: 1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 10.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0 Tempurature Range Of Tempurature Range Of Tempurature Rang	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power:  10.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 Tempurature Method:  160.0 Tempurature Method:	4.530 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  85.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius:  85.0 to 150.0 Inclosure Method:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 Inclosure Method:  Hermetically sealed  Ferminal Type:  Wire lead  Reliability Indicator:  Vot established  Ferminal Length:  1.500 inches  30dy Diameter:  2.250 inches  30dy Length:  2.750 inches  Power Dissipation Rating In Watts:  1.500 free air  Style Designator:  2.841 besignator:  2.8576-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  2.851 birth Gesure:  2.852 birth Gesure:  3.853 birth Gesure:  3.8545 birth Gesure:  3.855 birth Gesure:	-1.000 to 1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 150.0  Inclosure Method:  Hermetically sealed  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.050 inches  30dy Diameter:  1.050 inches  30dy Length:  1.0750 inches  30dy Length:  1.0750 inches  30dy Length:  1.0750 inches  30dy Length:  1.0750 inches  30dy Length:  3.050 free air  Style Designator:  Avial terminal each end  Test Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.:  20cculdes any specification, standard or other document that may be referenced in a basic governing drawing)  3cheff Life:  4.10  4.10  4.11	Ambient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 150.0  Inclosure Method: Idermetically sealed Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.500 inches 30dy Diameter: 0.250 inches 30dy Length: 0.750 inches 70wer Dissipation Rating In Watts: 1.500 free air 8tyle Designator: Avial terminal each end Fees Data Document: 18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Will Justic Of Measure:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 150.0  nclosure Method:  dermetically sealed  Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Ferminal Length:  1.500 inches  30dy Diameter:  2.250 inches  30dy Length:  3.750 inches  Power Dissipation Rating In Watts:  550 free air  Style Designator:  Axial terminal each end  Ferst Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  axial terminal each end  Fest Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  axial terminal each end  Fest Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  axial terminal each end  Fest Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  axial terminal each end  Fest Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  axial terminal each end  Fest Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  axial terminal each end  Fest Data Document:  18876-9158136 drawing (this is the basic governing drawing)  18876-9158136 drawing (this is the basic governing drawing)	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Hermetically sealed Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.500 inches 330dy Diameter: 1.250 inches 330dy Length: 1.570 inches Power Dissipation Rating In Watts: 1.550 free air Style Designator: Avail terminal each end Fest Data Document: 1.8876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2xxcludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Juit Of Measure:	150.0
Inclosure Method: Identically sealed Identically se	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.500 inches  30dy Diameter:  2.250 inches  30dy Length:  2.750 inches  Power Dissipation Rating in Watts:  2.500 fee air  Style Designator:  Avial terminal each end  Test Data Document:  1.8876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Via  Unit Of Measure:  - Demilitarization:  No	-55.0 to 150.0
Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Ferminal Length:  1.500 inches  30dy Diameter:  2.250 inches  30dy Length:  2.750 inches  Power Dissipation Rating In Watts:  3.500 Fee air  5tyle Designator:  Akala terminal each end  Fest Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  accludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	Inclosure Method:
Nice lead Reliability Indicator: Not established Ferminal Length: 1.500 inches Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Juit Of Measure: - Demilitarization: No	Hermetically sealed
Reliability Indicator: Not established Ferminal Length: 1.500 inches Body Diameter: 1.250 inches Body Length: 1.750 inches Power Dissipation Rating In Watts: 1.500 free air Style Designator: Axial terminal each end Fest Data Document: 18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Juit Of Measure: - Demilitarization: No	Terminal Type:
Not established Ferminal Length: 1.500 inches 30dy Diameter: 0.250 inches 30dy Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Ferst Data Document: 18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Wire lead
Terminal Length:  1.500 inches  30dy Diameter:  1.250 inches  30dy Length:  1.750 inches  20der Dissipation Rating In Watts:  1.500 free air  5tyle Designator:  Avail terminal each end  Fest Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  20xcludes any specification, standard or other document that may be referenced in a basic governing drawing)  3chelf Life:  3ch  4da Unit Of Measure:  - Demilitarization:	Reliability Indicator:
1.500 inches 3.0dy Diameter: 2.250 inches 3.0dy Length: 2.750 inches 3.0dy Length: 2.750 inches 3.0dy Length: 3.750 inches 3.0de Power Dissipation Rating In Watts: 3.500 free air 3.1500 free	Not established
Body Length: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Julit Of Measure:	Terminal Length:
2.250 inches  Body Length: 0.750 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end  Fest Data Document: 18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: - Demilitarization: No	1.500 inches
Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization:	Body Diameter:
Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Fest Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	0.250 inches
Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc., excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Body Length:
O.500 free air Style Designator: Axial terminal each end Fest Data Document: I 8876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization: No	0.750 inches
Axial terminal each end  Test Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end  Fest Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  1/a  Unit Of Measure:  Cemilitarization:	0.500 free air
Test Data Document:  18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Style Designator:
18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Test Data Document:
Shelf Life: N/a Unit Of Measure: - Demilitarization:	18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a  Jnit Of Measure:  -  Demilitarization:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Jnit Of Measure: - Demilitarization: No	Shelf Life:
- Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Filig:	No
	Fiig:
N001a0	A001a0