NSN 5905-00-845-6632

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-845-6632 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 0.359 inches and 0.391 inches **Terminal Length:** 0.437 inches **Body Diameter:** Between 0.734 inches and 0.766 inches **Body Length:** Between 0.359 inches and 0.391 inches **Overall Diameter:** 1.187 inches **Actuator Type:** Flush drive with slot-hole **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Unthreaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 2.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Tuneable by screwdriver slotted cover from either side of mtg surface **Terminal Type And Quantity:** 1 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

--

NSN 5905-00-845-6632

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



em			

No

Fiig:

A002a0