Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-846-2284

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.312 inches **Overall Height:** Between 0.297 inches and 0.328 inches **Overall Width:** Between 0.217 inches and 0.249 inches Mounting Hole Diameter: 0.088 inches Shaft Diameter: 0.093 inches Shaft Length: Between 0.047 inches and 0.078 inches **Body Length:** Between 1.234 inches and 1.266 inches **Body Width:** Between 0.217 inches and 0.249 inches **Body Height:** Between 0.297 inches and 0.328 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Maximum Starting Torque:** 7.00 inch-ounces Lateral Distance Between Mounting Hole Centers: Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:**

10.0 kilohms single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

7920.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Power Dissipation Rating Per Section In Watts:

0.8 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-2.0/+2.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

-

Demilitarization:

No

Fiig:

A002a0