

View Online at <https://aerobasegroup.com/nsn/5905-00-846-8707>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.6240 inches and 0.6250 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Undercut Diameter:

0.850 inches

Undercut Width:

Between 0.0570 inches and 0.0670 inches

Body Diameter:

0.938 inches

Shaft Diameter:

Between 0.094 inches and 0.156 inches

Shaft Length:

Between 0.644 inches and 0.706 inches

Body Length:

1.635 inches

Mounting Lip Diameter:

Between 0.8700 inches and 0.8800 inches

Mounting Lip Depth:

Between 0.0570 inches and 0.0670 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Contact Arm Electrical Off Position:

Fully ccw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.40 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.002 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Upper adjacent side two rows

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

3780.0

Function Conformity Tolerance Per Section:

-0.05/+0.05 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-40.0/+40.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

2 single section

Tap Location Tolerance Per Section:

-10.0/+10.0 ohms single section

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0