## NSN 5905-00-846-9288

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-846-9288 **Section Quantity: Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established **Overall Length:** Between 1.547 inches and 1.578 inches **Overall Height:** Between 0.375 inches and 0.406 inches **Overall Width:** Between 0.250 inches and 0.281 inches **Shaft Diameter:** 0.100 inches **Shaft Length:** 0.250 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** Between 1.297 inches and 1.328 inches **Body Width:** 0.266 inches **Body Height:** Between 0.310 inches and 0.330 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7920.0 **Screw Thread Diameter:** 0.190 inches **Screw Thread Series Designator:** Unf Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing

Humidity proof

**Features Provided:** 

## NSN 5905-00-846-9288

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0/+0.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A002a0