NSN 5905-00-847-6354

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-847-6354 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.8740 inches and 1.8750 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Undercut Diameter:** 1.688 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.812 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** Between 0.870 inches and 0.880 inches **Body Length:** Between 3.960 inches and 4.000 inches **Mounting Lip Diameter:** Between 1.9950 inches and 2.0050 inches **Mounting Lip Depth:** Between 0.0570 inches and 0.0670 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 1.40 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:**

0.002 inches

NSN 5905-00-847-6354



Precision Wire Wound Variable Resistor - Page 2 of 3
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.0 kilohms all sections
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
1800.0 all sections
Rotary Actuator Travel In Angular Deg:
Between 3960.0 and 3963.0
Function Conformity Tolerance Per Section:
-0.05/+0.05 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections
Power Dissipation Rating Per Section In Watts:
8.0 free air all sections
Function Conformity Per Section:
All sections absolute linearity
Fixed Tap Quantity Per Section:
1 all sections
Tap Location Tolerance Per Section:

-2.0/+2.0 ohms all sections

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 all sections

Actuator Travel Control Feature:

Stops

Tap Location From Ccw Terminal Per Section In Ohms:

5000.0 all sections

Function Characteristic Per Section:

All sections linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

NSN 5905-00-847-6354

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0