

View Online at <https://aerobasegroup.com/nsn/5905-00-848-5479>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.9750 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

1.000 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

1.062 inches

**Shaft Diameter:**

0.1248 inches

**Shaft Length:**

0.750 inches

**Body Length:**

0.750 inches

**Mounting Lip Diameter:**

1.0620 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round, slotted

**Contact Arm Electrical Off Position:**

Fully ccw

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

350.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

30.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

350.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0