Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-00-848-5516

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Pilot Diameter:

Between 0.74950 inches and 0.75000 inches

Pilot Length:

0.06200 inches

Terminal Length:

0.250 inches

Undercut Diameter:

0.781 inches

Undercut Width:

0.05700 inches

Shaft Diameter:

Between 0.1249 inches and 0.1250 inches

Shaft Length:

0.440 inches

Body Length:

1.000 inches

Mounting Lip Depth:

0.06200 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Double ended shaft

Shaft End Play:

0.00400 inches

Shaft Runout:

0.004 inches

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.00100 inches

Shaft Radial Play:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

NSN 5905-00-848-5516

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Features Provided: Nonmetallic shaft

Fixed Tap Quantity Per Section:

1 single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Special Features:

Second shaft 0.125 in. Nom Ig

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0