NSN 5905-00-848-8108

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-848-8108

20.0/+20.0 Electrical Resistance: 1.500 kilohms Resistance Tolerance in Percent: 2.5.00 Ambient Tempurature in Deg Celsius At Full Rated Power: 2.5.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 2.5.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 2.5.0 Fempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/+145.0 Fempurature Rethod: 6.0.000 6.000	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 0.1001/-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 0.250 inches 30dy Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: xxial terminal each end Fees Data Document: 91349-milr@3/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Jiht Of Measure: — Demilitarization: No	-20.0/+20.0
Resistance Tolerance in Percent: 0.100/+0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Implication Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Implication Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/+145.0 Implication Method: Implication Method: Implication Rating In Type: Wire lead Reliability Indicator: Not established 300dy Diameter: 1.250 inches 300dy Diameter: 1.250 inches Power Dissipation Rating in Watts: 1.250 inches Power Dissipation Rating in Watts: 1.250 free air Style Designator: Axial terminal each end Test Data Document: 1.349 -mill/39/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Juit Of Measure:	Electrical Resistance:
0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Vot established Body Diameter: 1,250 inches Body Length: 1,0750 inches Power Dissipation Rating In Watts: 1,050 inches Power Dissipation Rating In Watts: 1,050 free air Style Designator: 1,31345-millo3/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wia Jint Of Measure:	4.500 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Ratiability Indicator: Not established Body Diameter: 1.250 inches Body Length: 1.050 inches Power Dissipation Rating In Watts: 1.250 free air Style Designator: Xixial terminal each end Test Dat Document: 31494-millr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Julio Of Measure: - Demilitarization: No - Pilig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 1.250 free air Style Designator: Axial terminal each end Fest Data Document: 8349-milr3/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: Via Junit Of Measure: — Demilitarization: No	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/4145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avail terminal each end Test Data Document: 181349-mill/93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Diti Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Interport of the property of t	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/4145.0 nclosure Method: Encapsulated Ferminal Type: Write lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Julit Of Measure: - Demilitarization: No Elig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Diameter: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milit93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Juit Of Measure: Demilitarization: No Filig:	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: Bi31249-milip3/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Jinit Of Measure: - Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Skyle Designator: Availateminal each end Fest Data Document: B1349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: Via Jnit Of Measure:	-65.0/+145.0
Ferminal Type: Mire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avial terminal each end Fest Data Document: 81349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Are lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avial terminal each end Fest Data Document: 81349-millr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Juit Of Measure: - Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avial terminal each end Fest Data Document: 81349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Juit Of Measure: - Demilitarization: No Pigg:	Terminal Type:
Not established 3ody Diameter: 10.250 inches 3ody Length: 10.750 inches Power Dissipation Rating In Watts: 10.250 free air Style Designator: Avail terminal each end Fest Data Document: 13.349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Length: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Signification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Reliability Indicator:
2.250 inches 3.30dy Length: 2.750 inches 2.750 inches 2.750 inches 2.750 inches 2.750 inches 2.750 inches 2.750 fire air 3.750 inches 3	Not established
Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure: Demilitarization: No Filg:	Body Diameter:
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 31349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	0.250 inches
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 31349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Body Length:
Style Designator: Axial terminal each end Fest Data Document: B1349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	0.750 inches
Style Designator: Axial terminal each end Fest Data Document: 31349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 81349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fiig:	0.250 free air
Fest Data Document: 81349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formative excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Style Designator:
31349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-milr93/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Filg:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Jnit Of Measure: Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Filg:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Filg:	Demilitarization:
	No
\001a0	Fiig:
100 100	A001a0