NSN 5905-00-848-9440

No

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-848-9440

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|---|
| -260.0 to 260.0 |
| Electrical Resistance: |
| 24.000 ohms |
| Resistance Tolerance In Percent: |
| -5.000 to 5.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 350.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0 to 350.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.531 inches |
| Body Length: |
| 4.750 inches |
| Body Width: |
| 1.187 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 5.500 inches |
| Power Dissipation Rating In Watts: |
| 68.000 free air |
| Err Default: |
| 0.265 inches |
| Mounting Hole Size: |
| 0.196 inches |
| Style Designator: |
| Terminals one edge |
| Test Data Document: |
| 81349-mil-r-26/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 5905-00-848-9440

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0