NSN 5905-00-849-0686

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-849-0686

Electrical Resistance: 32.000 kilohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Axial terminal each end
32.000 kilohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
-0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
-65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator:
Power Dissipation Rating In Watts: 0.150 free air Style Designator:
0.150 free air Style Designator:
Style Designator:
Axial terminal each end
Test Data Document:
81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0